

ORDERING

SFX-800- - - - -K- - - - - - - -

Nominal diameter											
DN10 (3/8")	10										
DN15 (1/2")	15										
DN20 (3/4")	20										
DN25 (1")	25										
DN32 (1.25")	32										
DN40 (1.5")	40										
DN50 (2")	50										
DN65 (2.5")	65										
DN80 (3")	80										
DN100 (4")	1C										
DN125 (5")	1E										
DN150 (6")	1G										
DN200 (8")	2C										
DN250 (10")	2G										
DN300 (12")	3C										
DN350 (14")	3G										
DN400 (16")	4C										
DN450 (18")	4G										
DN500 (20")	5C										
DN600 (24")	6C										
DN700 (28")	7C										
DN800 (32")	8C										
DN900 (36")	9C										
DN1000 (40")	A0										
Process connection											
EN1092-1:2007 flange	L										
clamp	G										
ISO 2852 clamp	I										
ASME B16.5 flange	C										
JIS B2220 flange	S										
other	X										
Nominal pressure											
PN6	A										
PN10	B										
PN16	C										
PN25	D										
PN40	E										
PN63	F										
JIS 10K	J										
Class 150	G										
other	X										
Process connection material and body material											
carbon steel	MC										
304 stainless steel	M1										
other	XX										
Output and power supply											
4-20mA + pulse + RS-485, 230V AC	AA										
4-20mA + pulse + RS-485, 24V DC	AM										
4-20mA + HART + pulse + RS-485, 230V AC	AE										
4-20mA + HART + pulse + RS-485, 24V DC	AN										
4-20mA + pulse + RS-485 + SPST, 230V AC	AC										
4-20mA + pulse + RS-485 + SPST, 24V DC	AP										
4-20mA + HART + pulse + RS-485 + SPST, 230V AC	CE										
4-20mA + HART + pulse + RS-485 + SPST, 24V DC	CF										

